



# CHEMPLAX LLC

A KMI Group Company

Technical Data Sheet

## GenEVA EA28400

Ethylene Vinyl Acetate Copolymer

### Product Description

GenEVA EA28400 is an ethylene vinyl acetate resin.

Performance:

- Uniform VA & MI contents
- Excellent compatibility with other raw materials of HMA
- Good sensory characteristics

Applications:

- Hot Melt Adhesives

### Revision

Revision Date: 2/24/2025

Properties	Method	Value
Density	ASTM D1505	0.945 g/cm <sup>3</sup>
Melt Flow Rate (190°C/2.16kg)	ASTM D1238	400 g/10min
Vinyl Acetate Content	Internal Method	28wt.%
Tensile Properties	ASTM D638	
Tensile Strength (Break)		3 MPa
Tensile Elongation (Break)		900%
Melting Point	Internal Method	68°C
Durometer (Shore A)	ASTM D2240	68
Vicat Softening Temperature	ASTM D1525	<40°C

#### Notes

GenEVA EA28400 may be processed on conventional equipment.

**For additional inquiries, please contact: [csr.supplychain@kmigroup.com](mailto:csr.supplychain@kmigroup.com)**

TECHNICAL INFORMATION AND DATA REGARDING THE COMPOSITION, PROPERTIES OR USE OF THE PRODUCTS DESCRIBED HERE IS BELIEVED RELIABLE. HOWEVER NO REPRESENTATION OR WARRANTY IS MADE WITH RESPECT THERETO EXCEPT AS MADE BY CHEMPLAX LLC IN WRITING AT TIME OF SALE. CHEMPLAX LLC CANNOT ASSUME RESPONSIBILITY FOR ANY PATENT LIABILITY WHICH MAY RISE FROM THE USE OF ANY PBY CHEMPLAX LLC. RODUCT IN A PROCESS, MANNER OR FORMULA NOT DESIGNED